



Certificate of constancy of performance 0620-CPR-6065/02



Issued 2021-01-18

Replaces 0620-CPR-6065/01

First issued 2002-02-01

Pages 1 of 2

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Hose reels with semi-rigid hose

whereby the scope of construction product(s) is listed on page 2 of this certificate placed on the market under the name or trademark of

Meku B.V.

and produced in the manufacturing plant

MEKU BV - J H van Aismawei 72 – 74 - 9045 PM Beetgumermolen – The Netherlands

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN671-1:2012

under system 1 for the performances set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product**.

This certificate was first issued on February 1st, 2002 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273
P.O.Box 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
info@kiwa.nl
www.kiwa.nl

Company

Meku B.V.
J H Van Aismaweg 72-74
9045 PM BEETGUMERMOLLEN
The Netherlands
Tel. +31 58 253 1428
Fax +31 58 253 15 57
info@prolinemeku.com
www.prolinemeku.com

Aangewezen instantie Nr. 0620



Hose reels with semi-rigid hose

Hose Reel with Semi-rigid hose

Meku Model	Disc Diameter (mm)	Hose dimensions	Design
Pro-line	Maximum Ø 800	Ø 19 X maximum 30m	Manually operated
Pro-line	Maximum Ø 800	Ø 25 X maximum 30m	Manually operated
Pro-line	Maximum Ø 800	Ø 19 X maximum 30m	Automatically operated
Pro-line	Maximum Ø 800	Ø 25 X maximum 30m	Automatically operated

The hose reels with semi rigid hose with a dimension of 19 mm may be equipped with the following types of nozzle with a nominal diameter DN6:

- shot-jet nozzle, article no. 249808.9,
- plastic nozzle, article no. 109029.8,
- plastic nozzle **Pro-line**, fitted with a fluorescent outer ring

The hose reels with semi rigid hose with a dimension of 25 mm may be equipped with the following types of nozzle with a nominal diameter DN8:

- shot-jet nozzle, article no. 108999.0,
- plastic nozzle, article no. 102660.8,
- plastic nozzle **Pro-line**, fitted with a fluorescent outer ring

The Hose reel have been provided with:

- Semi rigid hose with a diameter of 19mm: **KIWA – MM – EN694:2014 – A – 2 – 19 – 1,2 – XQ/20XX**
- or
- Semi rigid hose with a diameter of 25mm: **KIWA – MM – EN694:2014 – A – 2 – 25 – 1,2 – XQ/20XX**

Furthermore the hose reels are provided with:

- Manual version: manually operated stop valve with valve or ball, provided with the Kiwa Mark
- or
- Automatic version: automatic shut-off valve, provided with the Kiwa Mark